

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

### 1 Identification

- **Product identifier**
- **Trade name: CERAMIC DURA GUARD**
- **Article number: K-441**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Kaady Chemical Corp.  
2118 Adams St.  
San Leandro, CA 94577  
+1-510-562-9785  
www.kaadychemical.com
- **Information department: Product safety department**
- **Emergency telephone number: 800-424-9300**

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Acute Tox. 4 H302 Harmful if swallowed.  
Skin Irrit. 2 H315 Causes skin irritation.  
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**  
2-butoxyethanol  
Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides  
PROPRIETARY
- **Hazard statements**  
Harmful if swallowed.  
Causes skin irritation.  
Causes serious eye irritation.
- **Precautionary statements**  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Wear protective gloves / eye protection / face protection.  
If swallowed: Call a poison center/doctor if you feel unwell.  
Rinse mouth.

(Contd. on page 2)

US

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 1)

If on skin: Wash with plenty of water.  
Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 0  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



HEALTH 1 Health = 1  
FIRE 0 Fire = 0  
REACTIVITY 0 Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

111-76-2	2-butoxyethanol	0-15%
61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	0-5%
	PROPRIETARY	0-10%
67-63-0	propan-2-ol	0-3%
556-67-2	octamethylcyclotetrasiloxane	0-1%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of 1910.1200 of 29 CFR 1910.1200 Trade Secrets.

### 4 First-aid measures

· **Description of first aid measures**

· **General information:** Immediately remove any clothing soiled by the product.

· **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 2)

If skin irritation occurs, seek medical advice.

- **After eye contact:**

Rinse opened eyes for at least 15 minutes under running water.

If easy to do so, remove contact lenses if worn.

Seek immediate medical advice.

- **After swallowing:**

Rinse out mouth and drink plenty of water or milk.

Do not induce vomiting without medical advice.

If vomiting does occur, repeat fluid administration.

If irritation or discomfort occurs, seek medical advice.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with the skin or eyes.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Avoid contact with the eyes, skin and clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

- **PAC-1:**

111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm

- **PAC-2:**

111-76-2	2-butoxyethanol	120 ppm
----------	-----------------	---------

(Contd. on page 4)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

**Trade name: CERAMIC DURA GUARD**

(Contd. of page 3)

67-63-0	propan-2-ol	2000* ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
<b>· PAC-3:</b>		
111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

**7 Handling and storage**

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**  
All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.
- **Components with limit values that require monitoring at the workplace:**  
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the other constituents have no known exposure limits.

**111-76-2 2-butoxyethanol**

PEL	Long-term value: 240 mg/m <sup>3</sup> , 50 ppm Skin
REL	Long-term value: 24 mg/m <sup>3</sup> , 5 ppm Skin
TLV	Long-term value: 97 mg/m <sup>3</sup> , 20 ppm BEI

**67-63-0 propan-2-ol**

PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 984 mg/m <sup>3</sup> , 400 ppm Long-term value: 492 mg/m <sup>3</sup> , 200 ppm BEI

(Contd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 4)

**556-67-2 octamethylcyclotetrasiloxane**

WEEL Long-term value: 10\* ppm  
\*OARS WEEL

· **Ingredients with biological limit values:**

**111-76-2 2-butoxyethanol**

BEI 200 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: Butoxyacetic acid with hydrolysis

**67-63-0 propan-2-ol**

BEI 40 mg/L  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Acetone (background, nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

(Contd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 5)

### 9 Physical and chemical properties

#### · Information on basic physical and chemical properties

##### · General Information

##### · Appearance:

Form:	Liquid
Color:	Amber colored
Odor:	Ether-like
Odor threshold:	Not determined.

##### · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point: Not applicable.

· Flammability (solid, gaseous): Not applicable.

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: Product does not present an explosion hazard.

##### · Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure: Not determined.

Density (Specific Gravity):	8.09
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.

##### · Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

##### · Viscosity:

Dynamic:	Not determined.
Kinematic:	Not determined.

##### · Solvent content:

Organic solvents:	Proprietary %
Water:	Proprietary %
VOC content:	10.5–12.3 %
	123.0 g/l / 1.03 lb/gal

(Contd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 6)

· **Other information** No further relevant information available.

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

#### ATE (Acute Toxicity Estimate)

Oral	LD50	1,135–1,265 mg/kg
Dermal	LD50	4,444 mg/kg (rab)
Inhalative	LC50/4 h	108–115 mg/l

#### 111-76-2 2-butoxyethanol

Oral	LD50	1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

#### 67-63-0 propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3

(Contd. on page 8)

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

**Trade name: CERAMIC DURA GUARD**

(Contd. of page 7)

- **NTP (National Toxicology Program)**  
None of the ingredients is listed.
- **OSHA-Ca (Occupational Safety & Health Administration)**  
None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.  
Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, ADN, IMDG, IATA** not regulated
- **UN proper shipping name**
- **DOT, ADN, IMDG, IATA** not regulated
- **Transport hazard class(es)**
- **DOT, ADN, IMDG, IATA**
- **Class** not regulated

(Contd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 8)

- |  |                        |
|--|------------------------|
| <b>· Packing group</b>   |                        |
| <b>· DOT, IMDG, IATA</b>   | <i>not regulated</i>   |
| <b>· Environmental hazards:</b>  | <i>Not applicable.</i> |
| <b>· Special precautions for user</b>  | <i>Not applicable.</i> |
| <b>· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b> | <i>Not applicable.</i> |
| <b>· UN "Model Regulation":</b>  | <i>not regulated</i>   |

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

<b>· Section 355 (extremely hazardous substances):</b>
--

<i>None of the ingredients is listed.</i>
---

<b>· Section 313 (Specific toxic chemical listings):</b>
--

111-76-2	2-butoxyethanol
----------	-----------------

67-63-0	propan-2-ol
---------	-------------

<b>· TSCA (Toxic Substances Control Act):</b>
---

111-76-2	2-butoxyethanol	ACTIVE
----------	-----------------	--------

61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	ACTIVE
------------	---	--------

67-63-0	propan-2-ol	ACTIVE
---------	-------------	--------

556-67-2	octamethylcyclotetrasiloxane	ACTIVE
----------	------------------------------	--------

7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
-----------	---	--------

<b>· Hazardous Air Pollutants</b>
-----------------------------------

<i>None of the ingredients is listed.</i>
---

<b>· Proposition 65</b>
-------------------------

<b>· Chemicals known to cause cancer:</b>
---

<i>None of the ingredients is listed.</i>
---

<b>· Chemicals known to cause reproductive toxicity for females:</b>
--

<i>None of the ingredients is listed.</i>
---

<b>· Chemicals known to cause reproductive toxicity for males:</b>
--

<i>None of the ingredients is listed.</i>
---

<b>· Chemicals known to cause developmental toxicity:</b>
---

<i>None of the ingredients is listed.</i>
---

<b>· Carcinogenic categories</b>
----------------------------------

<b>· EPA (Environmental Protection Agency)</b>
--

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

(Contd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

Trade name: CERAMIC DURA GUARD

(Contd. of page 9)

- **TLV (Threshold Limit Value established by ACGIH)**

111-76-2	2-butoxyethanol	A3
67-63-0	propan-2-ol	A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

2-butoxyethanol  
 Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides  
 PROPRIETARY

- **Hazard statements**

Harmful if swallowed.  
 Causes skin irritation.  
 Causes serious eye irritation.

- **Precautionary statements**

Wash thoroughly after handling.  
 Do not eat, drink or smoke when using this product.  
 Wear protective gloves / eye protection / face protection.  
 If swallowed: Call a poison center/doctor if you feel unwell.  
 Rinse mouth.  
 If on skin: Wash with plenty of water.  
 Specific treatment (see on this label).  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If skin irritation occurs: Get medical advice/attention.  
 Take off contaminated clothing and wash it before reuse.  
 If eye irritation persists: Get medical advice/attention.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- **Department issuing SDS:** Environment protection department.

- **Contact:** -

(Contd. on page 11)

US

**Safety Data Sheet**  
acc. to OSHA HCS

Printing date 09/19/2019

Reviewed on 09/19/2019

**Trade name: CERAMIC DURA GUARD**

(Contd. of page 10)

· **Date of preparation / last revision** 09/19/2019 / -· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
DOT: US Department of Transportation  
IATA: International Air Transport Association  
ACGIH: American Conference of Governmental Industrial Hygienists  
EINECS: European Inventory of Existing Commercial Chemical Substances  
ELINCS: European List of Notified Chemical Substances  
CAS: Chemical Abstracts Service (division of the American Chemical Society)  
NFPA: National Fire Protection Association (USA)  
HMIS: Hazardous Materials Identification System (USA)  
VOC: Volatile Organic Compounds (USA, EU)  
LC50: Lethal concentration, 50 percent  
LD50: Lethal dose, 50 percent  
PBT: Persistent, Bioaccumulative and Toxic  
vPvB: very Persistent and very Bioaccumulative  
NIOSH: National Institute for Occupational Safety  
OSHA: Occupational Safety & Health  
TLV: Threshold Limit Value  
PEL: Permissible Exposure Limit  
REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Acute Tox. 4: Acute toxicity – Category 4  
Skin Irrit. 2: Skin corrosion/irritation – Category 2  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· **\* Data compared to the previous version altered.**