

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

1 Identification

- **Product identifier**
- **Trade name:** CERAMIC PAINT PROTECTION
- **Article number:** K-441
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Kaady Chemical Corp.
2545 SW SPRING GARDEN ST STE 120
PORTLAND, OR 97219
+1-510-562-9788
www.kaadychemical.com
- **Information department:** Product safety department
- **Emergency telephone number:**
CHEMTREC 800-424-9300
ACCT# 12158

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

Acute Tox. 4 H302 Harmful if swallowed.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning
- **Hazard-determining components of labeling:**
Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides
2-butoxyethanol
PROPRIETARY
- **Hazard statements**
Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
- **Precautionary statements**
Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 1)

Do not eat, drink or smoke when using this product.

Wear protective gloves / eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin: Wash with plenty of water.

Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	<10%
111-76-2	2-butoxyethanol	<10%
67-63-0	propan-2-ol	<5%
	PROPRIETARY	2.5%
64-19-7	acetic acid	<2%

· **Additional information:**

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of 1910.1200 of 29 CFR 1910.1200 Trade Secrets.

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

If skin irritation occurs, seek medical advice.

Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eyes for at least several minutes under running water.

If easy to do so, remove contact lenses if worn.

Seek immediate medical advice.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:**

Rinse out mouth and drink plenty of water or milk.

Do not induce vomiting without medical advice.

If vomiting does occur, repeat fluid administration.

If irritation or discomfort occurs, seek medical advice.

Immediately call a doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Advice for firefighters**

- **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with the skin or eyes.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Avoid contact with the eyes, skin and clothing.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:** Dilute with plenty of water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 3)

Dispose contaminated material as waste according to item 13.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

111-76-2	2-butoxyethanol	60 ppm
67-63-0	propan-2-ol	400 ppm
64-19-7	acetic acid	5 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm
10043-52-4	calcium chloride	12 mg/m ³

PAC-2:

111-76-2	2-butoxyethanol	120 ppm
67-63-0	propan-2-ol	2000* ppm
64-19-7	acetic acid	35 ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
10043-52-4	calcium chloride	130 mg/m ³

PAC-3:

111-76-2	2-butoxyethanol	700 ppm
67-63-0	propan-2-ol	12000** ppm
64-19-7	acetic acid	250 ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm
10043-52-4	calcium chloride	790 mg/m ³

7 Handling and storage

Handling:

Precautions for safe handling No special precautions are necessary if used correctly.

Information about protection against explosions and fires: No special measures required.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep receptacle tightly sealed.

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 4)

Control parameters

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-76-2 2-butoxyethanol

PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 20 ppm BEI, A3

67-63-0 propan-2-ol

PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

64-19-7 acetic acid

PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 15 ppm Long-term value: 10 ppm

556-67-2 octamethylcyclotetrasiloxane

WEEL	Long-term value: 10* ppm *OARS WEEL
------	--

Ingredients with biological limit values:**111-76-2 2-butoxyethanol**

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid (BAA) (with hydrolysis)
-----	--

67-63-0 propan-2-ol

BEI	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-----	---

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 5)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Amber colored

· **Odor:** Ether-like

· **Odor threshold:** Not determined.

· **pH-value:** 12>

· **Change in condition**

Melting point/Melting range: Undetermined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 6)

Boiling point/Boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density (Specific Gravity):	8.09
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	- %
Water:	PROPRIETARY %
VOC content:	- %
-	-
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 7)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)		
Oral	LD50	1,101–1,237 mg/kg
Dermal	LD50	106,000 mg/kg (rabbit)
Inhalative	LC50/4 h	157 mg/l

111-76-2 2-butoxyethanol		
Oral	LD50	1,200 mg/kg (ATE) 1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)

67-63-0 propan-2-ol		
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

64-19-7 acetic acid		
Oral	LD50	3,310 mg/kg (rat)
Dermal	LD50	1,060 mg/kg (rabbit)

- Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - on the eye: Irritating effect.
 - Sensitization: No sensitizing effects known.
 - Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations:
- Harmful
- Irritant

- Carcinogenic categories

IARC (International Agency for Research on Cancer)		
111-76-2	2-butoxyethanol	3
67-63-0	propan-2-ol	3

NTP (National Toxicology Program)	
None of the ingredients is listed.	

OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 8)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 Water hazard class 3 (Self-assessment): extremely hazardous for water
 Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
 Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
 Observe all federal, state and local environmental regulations when disposing of this material.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADN, IMDG, IATA 	not regulated
<ul style="list-style-type: none"> · UN proper shipping name · DOT, ADN, IMDG, IATA 	not regulated
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT, ADN, IMDG, IATA · Class 	not regulated
<ul style="list-style-type: none"> · Packing group · DOT, IMDG, IATA 	not regulated
<ul style="list-style-type: none"> · Environmental hazards: 	Not applicable.
<ul style="list-style-type: none"> · Special precautions for user 	Not applicable.

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 9)

· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	not regulated

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture	No further relevant information available.	
· Sara		
· Section 355 (extremely hazardous substances):	None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):		
111-76-2	2-butoxyethanol	
67-63-0	propan-2-ol	
· TSCA (Toxic Substances Control Act):		
7732-18-5	water, distilled, conductivity or of similar purity	ACTIVE
541-02-6	2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane	ACTIVE
61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	ACTIVE
111-76-2	2-butoxyethanol	ACTIVE
102783-01-7	Dimethyl siloxane, ethoxylated, 3-hydroxypropyl-terminated	ACTIVE
67-63-0	propan-2-ol	ACTIVE
64-19-7	acetic acid	ACTIVE
556-67-2	octamethylcyclotetrasiloxane	ACTIVE
10043-52-4	calcium chloride	ACTIVE
· Hazardous Air Pollutants	None of the ingredients is listed.	
· Proposition 65		
· Chemicals known to cause cancer:	None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	None of the ingredients is listed.	

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 10)

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

111-76-2	2-butoxyethanol	NL
----------	-----------------	----

· **TLV (Threshold Limit Value)**

111-76-2	2-butoxyethanol	A3
----------	-----------------	----

67-63-0	propan-2-ol	A4
---------	-------------	----

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS07

· **Signal word** Warning· **Hazard-determining components of labeling:**

Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides

2-butoxyethanol

PROPRIETARY

· **Hazard statements**

Harmful if swallowed.

Causes skin irritation.

Causes serious eye irritation.

· **Precautionary statements**

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves / eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin: Wash with plenty of water.

Specific treatment (see on this label).

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 06/24/2025

Trade name: CERAMIC PAINT PROTECTION

(Contd. of page 11)

suitability of the material or product for any particular purpose.

· **Department issuing SDS:** Environment protection department.

· **Contact:** -

· **Date of preparation / last revision** 12/18/2024 / -

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

· *** Data compared to the previous version altered.**