

Printing date 12/18/2024

Reviewed on 6/26/2025

Page 1/10

### 1 Identification

- · Product identifier
- · Trade name: WEATHER REPELLANT
- · Article number: K-200A
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Kaady Chemical Corp. 2545 SW SPRING GARDEN ST STE 120 PORTLAND, OR 97219 +1-510-562-9788 www.kaadychemical.com
- Information department: Product safety department
   Emergency telephone number: CHEMTREC 800-424-9300 ACCT# 12158

## 2 Hazard(s) identification

· Classification of the substance or mixture



Acute Tox. 4 H302 Harmful if swallowed.

· Label elements

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- Hazard pictograms



· Signal word Warning

- *Hazard-determining components of labeling:* Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides 2-butoxyethanol
- · Hazard statements Harmful if swallowed.
- Precautionary statements
   Wash thoroughly after handling.
   Do not eat, drink or smoke when using this product.
   If swallowed: Call a poison center/doctor if you feel unwell.
   Rinse mouth.
   Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

<sup>—</sup> Us

Printing date 12/18/2024

Trade name: WEATHER REPELLANT

Classification system:
NFPA ratings (scale 0 - 4) Health = 1 Fire = 0 Reactivity = 0
HMIS-ratings (scale 0 - 4) Health = 1 Fire = 0 Reactivity = 0
Other hazards
Results of PBT and vPvB assessment PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
61789-77-3	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides	<10%		
111-76-2	111-76-2 2-butoxyethanol <10			
541-02-6	541-02-6 2,2,4,4,6,6,8,8,10,10-decamethylcyclopentasiloxane <10			
67-63-0	67-63-0 propan-2-ol <5%			

#### · Additional information:

The exact percentages of the ingredients of this mixture are considered to be proprietary and are withheld in accordance with the provisions of paragraph (i) of 1910.1200 of 29 CFR 1910.1200 Trade Secrets.

### 4 First-aid measures

#### Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.

Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

(Contd. on page 3)

us

(Contd. of page 1)

Reviewed on 6/26/2025

#### Page 3/10

## Safety Data Sheet acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 6/26/2025

#### Trade name: WEATHER REPELLANT

(Contd. of page 2)

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- Protective equipment:

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with the skin or eyes.

#### 6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Avoid contact with the eyes, skin and clothing. Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions:
- Dilute with plenty of water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. • Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.
- Protective Action Criteria for Chemicals

111-76-2 2-butoxyethanol	60 ppm
67-63-0 propan-2-ol	400 ppm
100-52-7 benzaldehyde	4 ppm
141-78-6 ethyl acetate	1,200 ppr
140-11-4 benzyl acetate	30 ppm
628-63-7 pentyl acetate	100 ppm
PAC-2:	
111-76-2 2-butoxyethanol	120 ppm
67-63-0 propan-2-ol	2000* ppr
100-52-7 benzaldehyde	9.9 ppm
141-78-6 ethyl acetate	1,700 ppn
140-11-4 benzyl acetate	330 ppm
628-63-7 pentyl acetate	670 ppm

Printing date 12/18/2024

Reviewed on 6/26/2025

#### Trade name: WEATHER REPELLANT

	(Contd. of page 3
· PAC-3:	
111-76-2 2-butoxyethanol	700 ppm
67-63-0 propan-2-ol	12000** ppm
100-52-7 benzaldehyde	59 ppm
141-78-6 ethyl acetate	10000** ppm
140-11-4 benzyl acetate	2,000 ppm
628-63-7 pentyl acetate	4000* ppm

## 7 Handling and storage

· Handling:

- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters

All ventilation should be disigned in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

#### • Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

111-	111-76-2 2-butoxyethanol		
PEL	Long-term value: 240 mg/m³, 50 ppm Skin		
REL	Long-term value: 24 mg/m³, 5 ppm Skin		
TLV	Long-term value: 20 ppm BEI, A3		
67-6	3-0 propan-2-ol		
PEL	Long-term value: 980 mg/m³, 400 ppm		
	(Contd. on page 5)		

Printing date 12/18/2024

Reviewed on 6/26/2025

## Trade name: WEATHER REPELLANT

			(Contd. of	f page
	Short-term value: 1225 mg/l Long-term value: 980 mg/m			
	• •	, 400 ppm		
	Short-term value: 400 ppm			
	Long-term value: 200 ppm			
	BEI, A4			
	dients with biological limi	values:		
	76-2 2-butoxyethanol			
	200 mg/g creatinine			
	Medium: urine			
	Time: end of shift Peremeter: Puterweestie esi	(BAA) (with hydrolysic)		
	Parameter: Butoxyacetic aci	(BAA) (With Hydrolysis)		
	8-0 propan-2-ol			
	40 mg/L Medium: urine			
	Time: end of shift at end of w	orkwook		
	Parameter: Acetone (backgr tional information: The list:	• •		
<b>Brea</b> <b>Prote</b> The g Due is chemisselece <b>Mate</b> <b>Mate</b> from matei <b>Pene</b> The e	to missing tests no recom ical mixture. stion of the glove material on <b>rial of gloves</b> selection of the suitable glove manufacturer to manufactur rial can not be calculated in a <b>tration time of glove mate</b> l	ed. rmeable and resistant to the nendation to the glove mai consideration of the penetra is does not only depend on t er. As the product is a prep idvance and has therefore to <b>ial</b> to be found out by the manu-	e product/ the substance/ the preparation. terial can be given for the product/ the preparation ation times, rates of diffusion and the degradation the material, but also on further marks of quality and paration of several substances, the resistance of the o be checked prior to the application. ufacturer of the protective gloves and has to be obse	l vari e glo
<b>D</b> /				
Pny	sical and chemical pro	perties		
	mation on basic physical a	nd chemical properties		
	eral Information			
	earance:			
For		Liquid		
Col	lor:	Dark blue		
Odor		Characteristic		
			(Contd. on	
			(contai on	i paye

Printing date 12/18/2024

## Trade name: WEATHER REPELLANT

		(Contd. of page
· Odor threshold:	Not determined.	
<ul> <li>Change in condition Melting point/Melting range: Boiling point/Boiling range:</li> </ul>	Undetermined. 100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits: Lower: Upper:	Not determined. Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
<ul> <li>Density (Specific Gravity):</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	Not determined. Not determined. Not determined. Not determined.	
Solubility in / Miscibility with Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.	
<ul> <li>Solvent content: Organic solvents: Water: VOC content:</li> </ul>	-* % PROPRIETARY % -* % -*	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

## 10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 7)

Reviewed on 6/26/2025

<sup>-</sup> US -

Printing date 12/18/2024

### Trade name: WEATHER REPELLANT

## · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

• Acute toxicity:

## · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)OralLD501,188–1,348 mg/kg

Inhalative LC50/4 h 220 mg/l

### 111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Dermal	LD50	400 mg/kg (rab)
67-63-0 pi	ropan-2-ol	1
Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

· Primary irritant effect:

· on the skin: No irritant effect.

· on the eye: No irritating effect.

· Sensitization: No sensitizing effects known.

· Additional toxicological information: Harmful

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)				
111-76-2	2-butoxyethanol	3		
67-63-0	propan-2-ol	3		
140-11-4	benzyl acetate	3		
97-53-0	Eugenol	3		
· NTP (National Toxicology Program)				
None of the ingredients is listed.				
· OSHA-Ca (Occupational Safety & Health Administration)				
None of the ingredients is listed.				

## **12 Ecological information**

· Toxicity

· Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

(Contd. on page 8)

Reviewed on 6/26/2025

(Contd. of page 6)

Page 8/10

(Contd. of page 7)

## Safety Data Sheet acc. to OSHA HCS

Printing date 12/18/2024

Reviewed on 6/26/2025

### Trade name: WEATHER REPELLANT

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

· vPvB: Not applicable.

· Other adverse effects No further relevant information available.

## 13 Disposal considerations

· Waste treatment methods

• Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Observe all federal, state and local environmental regulations when disposing of this material.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, IMDG, IATA	not requilated	
	not regulated	
UN proper shipping name DOT, IMDG, IATA	not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	not regulated	
Packing group		
DOT, IMDG, IATA	not regulated	
Environmental hazards:	Not applicable.	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex II of		
MARPOL73/78 and the IBC Code	Not applicable.	
UN "Model Regulation":	not regulated	

(Contd. on page 9)



Reviewed on 6/26/2025

Printing date 12/18/2024

(Contd. of page 8)

Page 9/10

#### Trade name: WEATHER REPELLANT

## 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

<ul> <li>Section 355 (extremel)</li> </ul>	hazardous substances):
--	------------------------

None of the ingredients is listed.

• Section 313 (Specific toxic chemical listings):

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

TSCA (Toxic Substances Control Act):

All components have the value ACTIVE.

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

• Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

111-76-2 2-butoxyethanol

• TLV (Threshold Limit Value)

111-76-2 2-butoxyethanol

67-63-0 propan-2-ol

140-11-4 benzyl acetate

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS). • **Hazard pictograms** 



(Contd. on page 10)

NL

A3

A4

A4



Printing date 12/18/2024

Reviewed on 6/26/2025

### Trade name: WEATHER REPELLANT

· Signal word Warning

- Hazard-determining components of labeling: Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides 2-butoxyethanol
- Hazard statements Harmful if swallowed.
- **Precautionary statements** Wash thoroughly after handling. Do not eat, drink or smoke when using this product. If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied, and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

- · Department issuing SDS: Environment protection department.
- · Contact: -
- Date of preparation / last revision 12/18/2024 / - Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Acute Tox. 4: Acute toxicity - Category 4

(Contd. of page 9)

Page 10/10

- US